

Advanced Technical Services

Lifecycle Solutions for Electronics

1-800-323-4813

info@ats4solutions.com

Absolyte GP

Type	Nominal Voltage	Capacities C ₈ @ 1.75 VPC @ 25°C	Dimensions approx.			Weight approx.
			L	W	H	
	V	Ah	in	in	in	Lbs
1-100G39	2	1800	20	8.55	26.4	329
1-100G45	2	2088	22.2	8.59	26.4	375
1-100G51	2	2400	24.5	8.59	26.4	424
1-100G57	2	2688	26.8	8.59	26.4	470
1-100G63	2	3000	29.1	8.59	26.4	516
1-100G69	2	3288	31.3	8.59	26.4	563
1-100G75	2	3600	33.6	8.59	26.4	609
1-100G81	2	3888	35.8	8.59	26.4	653
1-100G87	2	4200	38	8.59	26.4	704
1-100G93	2	4488	40.3	8.59	26.4	750
1-100G99	2	4800	42.6	8.59	26.4	796

ABSOLYTE GP
The Evolution of Power



From the needs of cable headend sites to the sale of replacement batteries for outside plant or Telecom sites, ATSS delivers solutions that are engineered to meet the highest standards of quality and delivery.

Advanced Technical Services

Lifecycle Solutions for Electronics

1-800-323-4813

info@ats4solutions.com

Absolyte GX

Type	Nominal Voltage	Capacities C ₈ @ 1.75 VPC @ 25°C	Dimensions approx.			Weight approx. lbs
			L in	W in	H in	
	V	Ah				
GX2000	4	2000	38.1	21.4	11.5	695
GX3000	4	3000	38.1	21.4	15.6	986
GX4000	4	4000	38.1	21.4	23	1389
GX5000	4	5000	38.1	21.4	27.1	1680
GX6000	4	6000	38.1	21.4	31.2	1971

ABSOLYTE GX
The Evolution of Power



Marathon M Bloc

Type	Nominal Voltage	Capacities 8 hr to 1.75 VPC @ 25°C	Dimensions approx.			Weight approx. Lbs
			L in	W in	H in	
	V	AH				
M6V190 ¹	6	190	12.05	6.85	8.8	74
M12V40 ¹	12	40	7.81	6.58	7.01	39
M12V70 ¹	12	72	10.25	6.85	8.8	61
M12V90 ¹	12	90	12.05	6.85	8.8	72

MARATHON®



From the needs of cable headend sites to the sale of replacement batteries for outside plant or Telecom sites, ATS delivers solutions that are engineered to meet the highest standards of quality and delivery.

Advanced Technical Services

Lifecycle Solutions for Electronics

1-800-323-4813

info@ats4solutions.com

Marathon FT Bloc

Type	Nominal Voltage	Capacities C_8 @ 1.75 VPC @ 25°C	Dimensions approx.			Weight approx.
			L	W	H	
	V	Ah	in	in	in	lbs
M12V90FT	12	86	15.55	4.13	10.63	70
M12V105FT	12	104	20.12	4.33	9.38	79
M12V125FT	12	125	22	4.9	11.15	105
M12V155FT	12	155	22	4.9	11.15	119
M12V180FT	12	180	22	4.9	12.5	133

MARATHON®



Relay Gel

Type	Nominal Voltage	Capacities C_8 @ 1.75 VPC @ 25°C	Reserve Capacity	Dimensions approx.			Weight approx.
				L	W	H	
	V	Ah	min	in	in	in	lbs
R12V22NF	12	46	85	8.99	5.55	8.12	38
R12V24	12	66	132	10.2	6.61	8.11	52.1
R12V27	12	78	155	12.1	6.61	8.11	62
R12V31	12	91	196	13	6.61	8.81	72.1

RELAY GEL®



From the needs of cable headend sites to the sale of replacement batteries for outside plant or Telecom sites, ATS delivers solutions that are engineered to meet the highest standards of quality and delivery.

Advanced Technical Services

Lifecycle Solutions for Electronics

1-800-323-4813

info@ats4solutions.com

Sprinter

Type	Nominal Voltage	Power	Dimensions approx.			Weight approx.
			L	W	H	
	V	WPC	in	in	in	lbs
S6V740 ¹	6	746	12.05	6.85	8.8	74
S12V170 ¹	12	167	7.81	6.58	7.01	36
S12V285 ¹	12	285	10.25	6.85	8.8	61
S12V300 ¹	12	306	10.25	6.85	8.8	63
S12V370 ¹	12	373	12.05	6.85	8.8	74
S12V500 ¹	12	505	13.55	6.76	10.56	106
S12V550 ¹	12	550	13.24	6.76	10.88	99



Classic MCT

Type	Nominal Voltage	Capacities	Dimensions approx.			Weight approx.
			L	W	H	
	V	Ah	in	in	in	lbs
2-MCT-5	4	192	6.26	11.2	18.3	106
MCT-7	2	288	4.14	11.2	18.3	70.6
MCT-9	2	384	5.12	11.2	18.3	88.2
MCT-11	2	480	6.5	11.2	18.3	109



From the needs of cable headend sites to the sale of replacement batteries for outside plant or Telecom sites, ATS delivers solutions that are engineered to meet the highest standards of quality and delivery.

Advanced Technical Services

Lifecycle Solutions for Electronics

1-800-323-4813

info@ats4solutions.com

Classic NXT

Type	Nominal Voltage	Capacities 1.215 SG C ₈ to 1.75 VPC @ 25°C	Dimensions approx.			Weight approx.
			L	W	H	
	V	Ah	in	in	in	lbs
NXT-09	2	621	7.37	14.5	22.2	140
NXT-11	2	753	7.37	14.5	22.2	154
NXT-13	2	874	7.37	14.5	22.2	167
NXT-15	2	986	7.37	14.5	22.2	180
NXT-17	2	1088	7.37	14.5	22.2	193
NXT-19	2	1181	7.37	14.5	22.2	205
NXT-21	2	1358	9.26	14.5	22.6	239
NXT-23	2	1475	9.26	14.5	22.6	252
NXT-25	2	1589	9.26	14.5	22.6	264
NXT-27	2	1753	11.4	14.5	22.6	301
NXT-29	2	1888	11.4	14.5	22.6	314
NXT-31	2	2141	14.6	14.5	22.6	373
NXT-33	2	2264	14.6	14.5	22.6	385
NXT-35	2	2385	14.6	14.5	22.6	399
NXT-37	2	2504	14.6	14.5	22.6	412
NXT-39	2	2620	14.6	14.5	22.6	425

GNB Flooded
Classic®



From the needs of cable headend sites to the sale of replacement batteries for outside plant or Telecom sites, ATIS delivers solutions that are engineered to meet the highest standards of quality and delivery.

Advanced Technical Services

Lifecycle Solutions for Electronics

1-800-323-4813

info@ats4solutions.com

Classic Flooded NCN

Type	Nominal Voltage	Capacities 1.215 SG C ₈ to 1.75 VPC @ 25°C/77°F	Dimensions approx.			Weight approx.
			L	W	H	
	V	Ah	in	in	in	lbs
NCN-7	2	552	7.37	14.5	22.2	159
NCN-9	2	688	7.37	14.5	22.2	177
NCN-11	2	824	7.37	14.5	22.2	197
NCN-13	2	952	7.37	14.5	22.2	214
NCN-15	2	1072	7.37	14.5	22.2	232
NCN-17	2	1200	7.37	14.5	22.2	247
NCN-19	2	1368	9.26	14.5	22.6	283
NCN-21	2	1496	9.26	14.5	22.6	303
NCN-23	2	1672	11.4	14.5	22.6	349
NCN-25	2	1808	11.4	14.5	22.6	364
NCN-27	2	1944	11.4	14.5	22.6	382
NCN-29	2	2152	14.6	14.5	22.6	448
NCN-31	2	2280	14.6	14.5	22.6	463
NCN-33	2	2416	14.6	14.5	22.6	481
NCN-35	2	2552	14.6	14.5	22.6	497

GNB Flooded **Classic**®



From the needs of cable headend sites to the sale of replacement batteries for outside plant or Telecom sites, ATS delivers solutions that are engineered to meet the highest standards of quality and delivery.

Advanced Technical Services

Lifecycle Solutions for Electronics

1-800-323-4813

info@ats4solutions.com

Classic H1T

Type	Nominal Voltage	Capacities 1.215 SG C ₈ to 1.75 VPC @ 25°C/77°F	Dimensions approx.			Weight approx.
			L in	W in	H in	
	V	Ah				lbs
H1T-23	2	2504	15.2	17.3	25.2	437
H1T-25	2	2640	15.2	17.3	25.2	453
H1T-27	2	2768	15.2	17.3	25.2	469
H1T-29	2	2904	15.2	17.3	25.2	485
H1T-31	2	3008	15.2	17.3	25.2	501
H1T-33	2	3112	15.2	17.3	25.2	517
H1T-35	2	3264	15.2	17.3	25.2	532
H1T-37	2	3416	15.2	17.3	25.2	548
H1T-39	2	3600	15.2	17.3	25.2	564
H1T-41	2	4000	15.2	17.3	25.2	580

GNB Flooded
Classic®



From the needs of cable headend sites to the sale of replacement batteries for outside plant or Telecom sites, ATSS delivers solutions that are engineered to meet the highest standards of quality and delivery.

Advanced Technical Services

Lifecycle Solutions for Electronics

1-800-323-4813

info@ats4solutions.com

Flooded TCXG

Type	Nominal Voltage	Capacities 1.215 SG C ₈ to 1.75 VPC @ 25°C/77°F	Dimensions approx.			Weight approx.
			L	W	H*	
	V	Ah	in	in	in	lbs
6-TCX-03G	12	50.4	10.71	8.11	15.4	77
6-TCX-05G	12	100	10.71	8.11	15.4	99
6-TCX-07G	12	147.2	14.96	8.11	15.4	141
3-TCX-09G	6	194.4	10.71	8.11	15.4	90
3-TCX-11G	6	237.6	14.96	8.11	15.4	123
3-TCX-13G	6	280.8	14.96	8.11	15.4	139
*Includes installed flame arrester						

GNB Flooded
Classic®



From the needs of cable headend sites to the sale of replacement batteries for outside plant or Telecom sites, ATS delivers solutions that are engineered to meet the highest standards of quality and delivery.

Advanced Technical Services

Lifecycle Solutions for Electronics

1-800-323-4813

info@ats4solutions.com

Classic MCX

Type	Nominal Voltage	Capacities 1.215 SG C ₈ to 1.75 VPC @ 25°C	Dimensions approx.			Weight approx.
			L	W	H	
	V	Ah	in	in	in	lbs
2-MCX-5	4	176	6.26	11.2	18.3	106
2-MCX-7	4	256	6.26	11.2	18.3	126
MCX-9	2	344	4.14	11.2	18.3	79.4
MCX-11	2	432	5.12	11.2	18.3	97.1
MCX-13	2	520	6.5	11.2	18.3	120
MCX-15	2	608	6.5	11.2	18.3	131

GNB Flooded
Classic



Sunlyte

Type	Nominal Voltage	Capacities 100 hr to 1.85 VPC @ 25°C	Dimensions approx.			Weight approx.
			L	W	H	
	V	AH	in	in	in	lbs
12-5000X	12	100	12.05	6.85	8.8	70

SUNLYTE



From the needs of cable headend sites to the sale of replacement batteries for outside plant or Telecom sites, ATS delivers solutions that are engineered to meet the highest standards of quality and delivery.

Advanced Technical Services

Lifecycle Solutions for Electronics

1-800-323-4813

info@ats4solutions.com

Sonnenschein A400

Type	Part number	Nom. Voltage V	Nominal capacity C 1.80 Vpc 20* C Ah	Max load approx A	Length (l) max. mm	Widt (b/w) max. mm	Height up to top of cover (h1) max. mm	Height over terminals (h2) max. mm	Weight approx. kg	Internal resistance mOhm	Short circuit current A	Terminal
A406/165 A	NGA4060165HSOCA	6	165	770	246	192	254	275	28	2.1	2800	A - Terminal
A406/165 F10	NGA4060165HS0FA	6	165	770	246	192	254	282	28.5	2.1	2800	F-M10
A412/5.5 SR	NGA41205D5HSORA	12	5.5	80	152	65.5	94.5	98.4	2.5	138	93	SR-6.3
A412/8.5 SR	NGA41208D5HSORA	12	8.5	80	152	98	94.5	98.4	3.6	86	150	SR-6.3
A415/12 SR	NGA4120012HSORA	12	12	100	181	76	152	157	5.6	47	260	SR-6.3
A412/20 G5	NGA4120020HS0BA	12	20	200	167	176	126	126	9	25	460	G-M5
A412/32 G6	NGA4120032HS0BA	12	32	400	210	175	175	175	13.6	15	784	G-M6
A412/32 F10	NGA4120032HS0FA	12	32	400	210	175	175	181	14.1	15	784	F-M10
A412/50 A	NGA4120050HSOCA	12	50	440	278	175	190	190	18.5	10	1220	A - Terminal
A412/50 F10	NGA4120050HS0FA	12	50	440	278	175	190	196	19	10	1220	F-M10
A412/50 G6	NGA4120050HS0BA	12	50	440	278	175	190	190	18.5	10	1220	G-M6
A412/65 F10	NGA4120065HS0FA	12	65	440	353	175	190	196	23.5	9	1414	F-M10
A412/65 G6	NGA4120065HS0BA	12	65	440	353	175	190	190	23	9	1414	G-M6
A412/85 F10	NGA4120085HS0FB	12	85	770	244	204	250	276	32	8	1472	F-M10
A412/90 A	NGA4120090HSOCA	12	90	770	284	267	208	230	33	7	1733	A - Terminal
A412/90 F10	NGA4120090HS0FA	12	90	770	284	267	208	237	33.5	7	1733	F-M10
A412/100 A	NGA4120100HSOCA	12	100	770	513	189	195	223	36.5	6.9	1777	A - Terminal
A412/100 F10	NGA4120100HS0FA	12	100	770	513	189	195	223	37	6.9	1777	F-M10
A412/120 A	NGA4120120HSOCA	12	120	770	513	223	195	223	45	5.7	2118	A - Terminal
A412/120 F10	NGA4120120HS0FA	12	120	770	513	223	195	223	45.5	5.7	2118	F-M10
A412/180 A	NGA4120180HSOCA	12	180	770	518	274	216	238	64	3.8	3227	A - Terminal
A412/180 F10	NGA4120180HS0FA	12	180	770	518	274	216	244	64.5	3.8	3227	F-M10



From the needs of cable headend sites to the sale of replacement batteries for outside plant or Telecom sites, ATS delivers solutions that are engineered to meet the highest standards of quality and delivery.

Advanced Technical Services

Lifecycle Solutions for Electronics

1-800-323-4813

info@ats4solutions.com

Sonnenschein A500

Type	Part number	Nom. Voltage V	Nominal capacity C 1.80 Vpc 20* C Ah	Max load approx A	Length (l) max. mm	Width (b/w) max. mm	Height up to top of cover (h1) max. mm	Height over terminals (h2) max. mm	Weight approx. kg	Internal resistance mOhm	Short circuit current A	Terminal
A502/10 S	NGA5020010HS0SA	2	10	80	52.9	50.5	94.5	98.4	0.7	11.2	189	S-4.8
A504/3.5 S	NGA50403D5HS0SA	4	3.5	60	90.5	34.5	60.5	64.4	0.5	48	88	S-4.8
A506/1.2 S	NGA50601D2HS0SA	6	1.2	40	97.3	25.5	51	55.6	0.33	165	38	S-4.8
A506/3.5 S	NGA50603D5HS0SA	6	3.5	60	135	34.8	60.5	64.4	0.7	71	88	S-4.8
A506/6.5 S	NGA50606D5HS0SA	6	6.5	80	152	34.5	94.5	98.4	1.3	48	131	S-4.8
A506/10 S	NGA5060010HS0SA	6	10	80	152	50.5	94.5	98.4	2.1	34	189	S-4.8
A508/3.5 S	NGA50803D5HS0SA	8	3.5	60	179	34.1	60.5	64.4	1	95	88	S-4.8
A512/1.2 S	NGA51201D2HS0SA	12	1.2	40	97.5	49.5	51	54.9	0.65	330	38	S-4.8
A512/2 S	NGA5120002HS0SA	12	2	40	179	34.1	60.5	64.4	1	172	73	S-4.8
A512/3.5 S	NGA51203D5HS0SA	12	3.5	60	135	66.8	60.5	64.4	1.5	142	88	S-4.8
A512/6.5 S	NGA51206D5HS0SA	12	6.5	80	152	65.5	94.5	98.4	2.6	95	131	S-4.8
A512/10 S	NGA5120010HS0SA	12	10	80	152	98	94.5	98.4	4	66	189	S-4.8
A512/16 G5	NGA5120016HS0BA	12	16	200	181	76	167	167	6	37.8	340	G-M5
A512/25 G5	NGA5120025HS0BA	12	25	200	167	176	126	126	9.6	28	463	G-M5
A512/30 G6	NGA5120030HS0BA	12	30	400	197	132	161	180	11.1	21.8	586	G-M6
A512/40 A	NGA5120040HS0CA	12	40	400	210	175	175	175	14.2	16.5	770	A-Terminal
A512/40 G6	NGA5120040HS0BA	12	40	400	210	175	175	175	14.2	16.5	770	G-M6



From the needs of cable headend sites to the sale of replacement batteries for outside plant or Telecom sites, ATS delivers solutions that are engineered to meet the highest standards of quality and delivery.

Advanced Technical Services

Lifecycle Solutions for Electronics

1-800-323-4813

info@ats4solutions.com

Sonnenschein A500 continued

Type	Part number	Nom. Voltage V	Nominal capacity C 1.80 Vpc 20* C Ah	Max load approx A	Length (l) max. mm	Width (b/w) max. mm	Height up to top of cover (h1) max. mm	Height over terminals (h2) max. mm	Weight approx. kg	Internal resistance mOhm	Short circuit current A	Terminal
A512/55 A	NGA5120055HS0CA	12	55	400	261	135	208	230	18.1	10.9	1147	A-Terminal
A512/60 A	NGA5120060HS0CA	12	60	400	278	175	190	190	20.8	14	936	A-Terminal
A512/60 G6	NGA5120060HS0BA	12	60	400	278	175	190	190	20.8	14	936	G-M6
A512/65 A	NGA5120065HS0CA	12	65	400	353	175	190	190	23.5	8.3	1471	A-Terminal
A512/65 G6	NGA5120065HS0BA	12	65	400	353	175	190	190	23.5	8.3	1471	G-M6
A512/85 A	NGA5120085HS0CA	12	85	600	330	171	213	236	29.2	7.4	1693	A-Terminal
A512/115 A	NGA5120115HS0CA	12	115	770	286	269	208	230	37.5	5.5	2275	A-Terminal
A512/120 A	NGA5120120HS0CA	12	120	770	513	189	195	223	40	5.1	2475	A-Terminal
A512/140 A	NGA5120140HS0CA	12	140	770	513	223	195	223	47	4.1	3132	A-Terminal
A512/200 A	NGA5120200HS0CA	12	200	770	518	274	216	238	67	3.8	3370	A-Terminal



From the needs of cable headend sites to the sale of replacement batteries for outside plant or Telecom sites, ATS delivers solutions that are engineered to meet the highest standards of quality and delivery.

Advanced Technical Services

Lifecycle Solutions for Electronics

1-800-323-4813

info@ats4solutions.com

Sonnenschein A600

Type	Part number	Type acc. To DIN 40 742 DIN 40 744	Nom. Voltage	nominal capacity C 1.8 Vpc 20 C Ah	Length (l) max. mm	Width (b/w) max. mm	Height (h1) max. mm	Height (h2) max. mm	Weight approx kg	Internal resistance mOhm	Short circuit current A	Terminal	Pole Pairs
A602/225	NGA6020225GS0FA	4 OPzV 200	2	224	105	208	357	399	19	0.95	2200	F-M8	1
A602/280	NGA6020280HS0FA	5 OPzV 250	2	280	126	208	357	399	23	0.79	2700	F-M8	1
A602/335	NGA6020335HS0FA	6 OPzV 300	2	337	147	208	357	399	27	0.61	3350	F-M8	1
A602/415	NGA6020415GS0FA	5 OPzV 350	2	416	126	208	473	515	30	0.62	3300	F-M8	1
A602/500	NGA6020500HS0FA	6 OPzV 420	2	499	147	208	473	515	35	0.53	3950	F-M8	1
A602/580	NGA6020580HS0FA	7 OPzV 490	2	582	168	208	473	515	39	0.47	4400	F-M8	1
A602/750	NGA6020750HS0FA	6 OPzV 600	2	748	147	208	648	690	49	0.48	4300	F-M8	1
A602/1010	NGA6021010HS0FA	8 OPzV 800	2	998	212	193	348	690	66	0.38	4850	F-M8	2
A602/1250	NGA6021250HS0FA	10 OpzV 1000	2	1248	212	235	348	690	80	0.33	6250	F-M8	2
A602/1510	NGA6021510HS0FA	12 OpzV 1200	2	1497	212	277	348	690	95	0.29	7850	F-M8	2
A602/1650C	NGA6021650HS0FA	12 OPzV 1500	2	1643	212	277	717	759	115	0.23	9000	F-M8	2
A602/2200	NGA6022200HS0FA	16 OPzV 2000	2	2190	216	400	775	816	160	0.19	10750	F-M8	3
A602/2740	NGA6022740HS0FA	20 OPzV 2500	2	2738	214	489	774	816	198	0.16	13400	F-M8	4
A602/3300	NGA6023300HS0FA	24 OPzV 3000	2	3286	214	578	774	816	238	0.1	16100	F-M8	4
A606/200	NGA6060200HS0FB	6V 4 OpzV 200	6	200	272	206	323	347	45.7	2.71	1707	F-M8	1
A606/300	NGA6060300HS0FB	6V 6 OpzV 300	6	300	380	206	323	347	65.4	1.9	2614	F-M8	1
A612/100	NGA6120100HS0FB	12V 2 OpzV 100	12	100	272	206	323	347	46.2	9.68	1934	F-M8	1
A612/150	NGA6120150HS0FB	12V 3 OpzV 150	12	150	380	206	323	347	66.9	6.43	2896	F-M8	1



From the needs of cable headend sites to the sale of replacement batteries for outside plant or Telecom sites, ATS delivers solutions that are engineered to meet the highest standards of quality and delivery.

Advanced Technical Services

Lifecycle Solutions for Electronics

1-800-323-4813

info@ats4solutions.com

Sonnenschein A700

Type	Part number	Nom. Voltage V	Nominal capacity C 1.80 Vpc 20* C Ah	Max load approx A	Length (l) max. mm	Widt (b/w) max. mm	Height up to top of cover (h1) max. mm	Height over terminals (h2) max. mm	Weight approx. kg	Internal resistance mOhm	Short circuit current A	Terminal
A704/245	NGA7040245HS0FB	4V 7 0GiV 224	4	245	250	232	296	327	35.5	1.7	3181	F-M6
A704/280	NGA7040280HS0FB	4V 8 0GiV 256	4	280	250	232	296	327	37.5	1.17	3490	F-M6
A706/63	NGA7060063HS0FB	6V 3 0GiV 54	6	63	198	178	241	272	16.3	5.8	1058	F-M6
A706/84	NGA7060084HS0FB	6V 4 0GiV 72	6	84	198	178	241	272	18.3	4.3	1409	F-M6
A706/105	NGA706105HS0FB	6V 5 0GiV 90	6	105	282	178	241	272	24.5	3.6	1726	F-M6
A706/126	NGA7060126HS0FB	6V 6 0GiV 108	6	126	282	178	241	272	26.2	2.9	2092	F-M6
A706/140	NGA7060140HS0FB	6v 4 0GiV 128	6	140	285	232	296	327	36.3	3	2083	F-M6
A706/175	NGA7060175HS0FB	6v 5 0GiV 160	6	175	285	232	296	327	39.7	2.6	2383	F-M6
A706/210	NGA7060210HS0FB	6v 6 0GiV 192	6	210	285	232	296	327	42.9	2.2	2876	F-M6



From the needs of cable headend sites to the sale of replacement batteries for outside plant or Telecom sites, ATS delivers solutions that are engineered to meet the highest standards of quality and delivery.

Advanced Technical Services

Lifecycle Solutions for Electronics

1-800-323-4813

info@ats4solutions.com

Sonnenschein Solar

Type	Part number	Nom. Voltage V	Nominal capacity C 1.80 Vpc 20* C Ah	discharge current I100 A	Length (l) max. mm	Width (b/w) max. mm	Height up to top of cover (h1) max. mm	Height including connector s (h2) max. mm	Weight approx. kg	terminal approx kg	terminal position
S12/6.6 S	NGS01206D6HS0SA	12	6.6	0.06	152	65.5	94.5	98.4	2.6	S-4.8	3
S12/17 G5	NGS0120017HS0BA	12	17	0.17	181	76		167	6.1	G-M5	1
S12/27 G5	NGS0120027HS0BA	12	27	0.27	167	176		126	9.6	G-M5	1
S12/32 G6	NGS0120032HS0BA	12	32	0.32	197	132	160	184	11.1	G-M6	2
S12/41 A	NGS0120041HS0CA	12	41	0.41	210	175		175	14.2	A-Terminal	1
S12/60 A	NGS0120060HS0CA	12	60	0.6	261	136	208	230	18.1	A-Terminal	1
S12/85 A	NGS0120085HS0CA	12	85	0.85	353	175		190	26.8	A-Terminal	1
S12/90 A	NGS0120090HS0CA	12	90	0.9	330	171	213	236	29.2	A-Terminal	2
S12/130 A	NGS0120130HS0CA	12	130	1.3	286	269	208	230	37.5	A-Terminal	4
S12/230 A	NGS0120230HS0CA	12	230	2.3	518	274	216	238	67	A-Terminal	3



From the needs of cable headend sites to the sale of replacement batteries for outside plant or Telecom sites, ATS delivers solutions that are engineered to meet the highest standards of quality and delivery.

Advanced Technical Services

Lifecycle Solutions for Electronics

1-800-323-4813

info@ats4solutions.com

Sonnenschein Solar Bloc

Type	Part number	Nom. Voltage v	Nominal capacity C 1.80 Vpc 20* C Ah	discharge current I100 A	Length (l) max. mm	Width (b/w) max. mm	Height up to top of cover (h1) max. mm	Height including connector s (h2) max. mm	Weight approx. kg	terminal approx kg	terminal position
SB 6/200	NGSB060200HSOCA	6	200	2	246	192	254	275	29	A-Terminal	4
SB 6/330 A	NGSB060330HSOCA	6	330	3.3	312	182	337	359	47	A-Terminal	4
SB12/60 A	NGSB120060HSOCA	12	60	0.6	278	175		190	19	A-Terminal	1
SB12/75 A	NGSB120075HSOCA	12	75	0.75	330	171	214	236	28.8	A-Terminal	2
SB12/100 A	NGSB120100HSOCA	12	100	1	513	189	195	223	36.5	A-Terminal	3
SB12/130 A	NGSB120130HSOCA	12	130	1.3	513	223	195	223	45.5	A-Terminal	3
SB12/185 A	NGSB120185HSOCA	12	185	1.85	518	274	216	238	61.5	A-Terminal	3



From the needs of cable headend sites to the sale of replacement batteries for outside plant or Telecom sites, ATS delivers solutions that are engineered to meet the highest standards of quality and delivery.

Advanced Technical Services

Lifecycle Solutions for Electronics

1-800-323-4813

info@ats4solutions.com

Sonnenschein A600 Solar

Type	Part number	Nom. Voltage V	Nominal capacity C 1.80 Vpc 20* C Ah	discharge current I100 A	Length (l) max. mm	Width (b/w) max. mm	Height up to top of cover (h1) max. mm	Height including connector s (h2) max. mm	Weight approx. kg	terminal	pole pairs
A602/295 SOLAR	NGS6020295HS0FC		2	294	2.45	105	357	399	19	F-M8	1
A602/370 SOLAR	NGS6020370HS0FC		2	367	3.05	126	357	399	23	F-M8	1
A602/440 SOLAR	NGS6020440HS0FC		2	440	3.66	147	357	399	27	F-M8	1
A602/520 SOLAR	NGS6020520HS0FC		2	519	4.32	126	473	515	30	F-M8	1
A602/625 SOLAR	NGS6020625HS0FC		2	623	5.19	147	473	515	35	F-M8	1
A602/750 SOLAR	NGS6020750HS0FC		2	727	6.05	168	473	515	39	F-M8	1
A602/850 SOLAR	NGS6020850HS0FC		2	845	7.06	147	648	690	49	F-M8	1
A602/1130 SOLAR	NGS6021130HS0FC		2	1126	9.42	212	648	690	66	F-M8	2
A602/1415 SOLAR	NGS6021415HS0FC		2	1408	11.7	212	648	690	80	F-M8	2
A602/1695 SOLAR	NGS6021695HS0FC		2	1689	14.1	212	648	690	95	F-M8	2
A602/1960C SOLAR	NGS6021960HS0FC		2	1994	16.3	212	717	759	115	F-M8	2
A602/2600 SOLAR	NGS6022600HS0FC		2	2613	21.7	216	775	816	160	F-M8	3
A602/3270 SOLAR	NGS6023270HS0FC		2	3266	27.2	214	774	816	198	F-M8	4
A602/3920 SOLAR	NGS6023920HS0FC		2	3919	32.6	214	774	816	238	F-M8	4



From the needs of cable headend sites to the sale of replacement batteries for outside plant or Telecom sites, ATS delivers solutions that are engineered to meet the highest standards of quality and delivery.